



DIGITAL TENSION METER TT900



APPLICATION:

Digital Tension Meter is a hand-held device which accurately measures the running as well as static tensions of a wide variety of process materials including yarns, fibers, wires, optical fibers, etc.

SPECIFICATION:

Tension Range	0~2.0kgf 0~2000gf
	0~19.6N
	0~4.4Lbf
	0.001kgf
Resolution	1gf
	0.01N
	0.001Lbf
Accuracy	±1.5% or better

Unit	kgf, gf, N, Lbf
Measuring Principle	Strain gauge
Measuring Frequency	16 msec (62.5 samples/sec)
Sensing Roller	Deflection of Sensing Roller (max.) 0.2mm
Overload Capacity	150% of Full Scale
Temperature	Zero: less than +0.3% FS/°C
Coefficient	Span: less than +0.01% FS/°C
Display	Blue Back light LCD
Display Update Rate	0.5, 1.0, 2.0 or 4.0 seconds, selectable

Current Value, Max. Value,
Peak Value, Min Value
Buzzer Alarm
10 Minutes Auto, Manual
USB, Bluetooth
Stainless Steel (Standard)
Plastic (Optional)
2000m/min
4x1.5 AAA(UM-4) Battery
0~40°C
<80%
400g
Main Unit: 149x70x30mm
Sensor: 102x81x34mm

FEATURES:

- It employs the 'three-roller principle' of tension test.
- High accuracy and high resolution.
- Digital display with no guessing or errors.
- Power is supplied by 4xAAA alkaline battery.
- With 4 measurement unit for selection, N, kg, lb, g.
- Current Value, Max. Value, Peak Value, Min Value can be displayed at the same time.
- With 10 minutes auto power off and manual power off.
- The Meter takes 62 tension measurements per second and displays the average of these measurements.
- With data output, by USB cable or Bluetooth adapter.